

3- (2,3-Epoxypropoxy)propyltriethoxysilane (KH560)

Features of 3- (2,3-Epoxypropoxy)propyltriethoxysilane (KH560) China

- Product Name: 3- (2,3-Epoxypropoxy)propyltriethoxysilane) (KH560)
- Chemical Formula: (KH560)
- CAS No.: 2602-34-8
- Dangerous Grade: 3

Technical Data of 3- (2,3-Epoxypropoxy)propyltrimethoxysilane

| ITEMS | SPECIFICATION |
|-----------------------------------|------------------------------|
| Appearance | Colorless transparent liquid |
| Reactive index(n _{25D}) | 1.4270±0.0050 |
| Assay | 97% |

Package and Storage:

- 200kg/drum or 1000kg/IBC drum
- Store in a cool, dry place. Keep container closed when not in use

Application /Application Industries:

- Glass fiber rovings
- Packing materials

- Coating

CG-O1871 Typical Benefits: Improves dry and wet strength in cured composites reinforced with glass fiber rovings. Enhances wet electrical properties of epoxy-based encapsulate and packaging materials. Eliminates the need for a separate primer in polysulfide and urethane sealants. Improves adhesion in waterborne acrylic sealants and in urethane and epoxy coatings.

Nanjing Chemical Material Corp.

ADD: 12/F, Block B, Technology and Innovation Building, Nanjing University of

Technology, No.5 New Model Road, Nanjing 210009, China

Tel: 86-25-52337978

Fax: 86-25-83304509

E-mail: info@njchm.com