

Polyether Polyol 12000

Features of Polyether Polyol 12000

- Product Name: Polyether Polyol 12000
- Chemical Formula: N/A
- CAS No.: N/A
- Dangerous Grade: NO

Technical Data of Polyether Polyol 12000

ITEMS	SPECIFICATION
Appearance	Transparent
Colority(APHA)	≤50
Hydroxyl value(KOH mg/g)	9.5±1
Viscosity(mPa·s, 25°C)	4000-8000
Water content(%)	≤0.05
Acid value(KOH mg/g)	≤0.08
PH value	5-8

Package and Storage:

- 200kg/drum or 1000kg/IBC drum
- Store in a cool, dry place. Keep container closed when not in use

Application /Application Industries:

- PU foams

The polyether polyols with their molecular weight 6000 — 20000 have the properties of low viscosity, and narrow molecular weight distribution relatively with so high molecular weight. Nanjing Chemical Material Corp. can produce the polyether polyols according to the requirement of customers.

High flashpoint, flammable. Explosion: no explosion. Use foam, powder, steam and water to put out when it is Firing. Toxicity: almost nonpoisonous. If the products splash on the skin or in the eyes, it must be washed immediately with plenty of water or go to see the doctor.

The products are stored in ventilated and dry warehouse storage at Room temperature. The period of storage is a year. If the specifications are good, it can be used again after a year. Prevent them from rain and relief lightly in transportation. Be sure not to turn upside down. Steel drums with zinc-plated which weight is 200kg.